



Works Wonder for your Business !!

### **1. REST - API using Authorisation Token:**

To provide flexible and secured way of communicating through API, we have developed Authentication Token Based REST-APIs for our Bulk SMS Service.

We have given complete documentation in Swagger where you can test the APIs also.

This will work by generating **Authorisation Token** which will be further passed in Header of each API call.

### **Quick Start Guide For Testing in Swagger:**

1. Go to: <https://businesssms.co.in/swagger/index.html> (Alternatively, BusinessSMS Partners having Hosted Panel can replace <https://businesssms.co.in> with their sub-domain name.)
2. Pass User id and password in **AuthTokenV1/AuthToken** .
3. Copy Bearer Authentication token received in **TxnOutcome** to **Authorize** button given at top right corner.
4. Now you can test other APIs to check the services .Here, Bearer Authentication Token will be implicitly passed in header of API calls.

### **List of available API:**

Type	API	Description	Response
<b>AuthTokenV1</b>			
GET or POST	AuthTokenV1/ AuthToken	Users of the REST API can authenticate by providing a user ID and password. Authorisation/Bearer token is generated to enable to authenticate future requests	Returns BEARER Authentication token which should be passed in Header of other API listed below and is valid for 6 Hours.
<b>Health</b>			
GET	Health	States Reachability of SMS Portal	Reachability



Works Wonder for your Business !!

<b>SMSV1</b>			
POST	SMSV1/SubmitSMS	Post/Sent SMS to Phone number. senderID, dlrUrl, scheduleAt, pe are optional parameters here.	Submits SMS and returns SMS submitted, balance used, no of segments, SMS balance etc.
GET	SMSV1/UserAccDetails	Get SMS account details using which Authentication Token was generated.	details like Balance, Expiry Date etc.
GET	SMSV1/GetOTPForChange Pwd	Get OTP to change Password of the SMS account.	OTP
POST	SMSV1/ChangePassword	Change Password of SMS account by providing OTP received in <i>GetOTPForChangePwd</i>	New password will be reset to account
<b>TxnLogV1</b>			
GET	TxnLogV1/DailySummary	Get Summary of SMS Submitted from date range. For getting summary of single date, just mention it in 'FromDate' Parameter.	Summary of Sent, Submitted, Delivered SMS.



Works Wonder for your Business !!

## **2. BusinessSMS HTTP API Specifications**

Users, who wish to send message-using HTTP (Hyper Text Transfer Protocol) features or develops applications using the BusinessSMS Gateway for sending SMS messages. Gateway can be accessed through HTTP protocol by submitting values by GET or POST method.

### **Sample URL to Submit SMS:**

<https://www.businesssms.co.in/sms.aspx?ID=XXXX&Pwd=YYYY&PhNo=91XXXXXXXXXX,91XXXXXXXXXX&Text=MessageText&TemplateID=<DLT Registered SMS Template ID>&ScheduleAt=25/03/2009+04%3A00+PM>

### **Sample URL to Check Account Balance:**

<https://www.businesssms.co.in/sms.aspx?ID=XXXX&Pwd=YYYY>

### **2.1 HTTP Parameters for SMS Submission**

Parameter Name	Possible Values / Function
ID	Set BusinessSMS Account UserID
Pwd	Set BusinessSMS account Password
PhNo	Comma delimited list of phone numbers (Limit to max 100 Nos. per http invoke.)  All numbers must start with Country Code (91 for India) - Message may not get delivered if Country Code is not added to numbers submitted to this HTTP API
Text	Actual Message text. Length of single SMS is 160 characters. GSM handsets provides capability to receive long SMS (multi-segment) with each segment being 152 characters and SMS gets re-assembled and displayed as single SMS by receiving GSM handset. If SMS contains single Unicode character, complete SMS would be sent as Unicode SMS with 70 chars as single SMS size and 64 chars as segment size in case of multi segment Unicode SMS.
ScheduleAt (Optional)	Future Schedule Date and Time ( <u>Max 365 days in future</u> )  If included, SMS would be scheduled for delivery at a later date time indicated by this parameter.  Format: "DD/MM/yyyy hh:mm tt"
SenderID (Optional)	By default, SenderID parameter disabled for all clients. Based on the business agreements with client, this feature can be enabled so that client can set their own SenderID for message delivery. 8 Char alphanumeric SenderID (3 Char routing information would be prefixed to this).



## Works Wonder for your Business !!

**DirUrl**  
(Optional) Set DirUrl parameter to get back delivery status on HTTP. DirUrl should also have MsgID set to ID of sms in your system. When BusinessSMS Server received delivery report from operator, DirUrl would be invoked by BusinessSMS server by adding status parameter to same DirUrl (which you have provided along with MsgID at the time of sms submission.) Use only one mobile number in HTTP API Invocation for Dlr over HTTP to work properly.

Example DirUrl value:

&DirUrl=http://www.mysmswebsite.com/InBSDlr.aspx?MsgID=<ID of this sms in your system>

Example HTTP Request (from your server):

<https://www.businesssms.co.in/sms.aspx?ID=abc@prq.com&Pwd=pwd&PhNo=91xxxxxxxxxx&Text=HTTP-Sample-SMS-with-Dlr-Url&DirUrl=http://www.mydomain.in/sms/inbsdldr.aspx?msgid=ef56da43>

Note: For this to work you must have webpage highlighted in gray above in place. This page will read parameters 'msgid' and 'status' and update in your database.

Example HTTP Invocation of DirUrl form BusinessSMS Server:

<http://www.mydomain.in/sms/inbsdldr.aspx?msgid=ef56da43&status=DELIVERD>

**SMSType**  
(Optional) 0: Normal (Default, if this parameter not specified)  
1: Flash SMS  
3: WAP SI – Text format same as in BusinessSMS Web appl.  
4: VCard – Text format same as in BusinessSMS web appl.  
6: Picture SMS – <Registered PictureID>:MessageText..

**PE**  
(Optional) Principal Entity ID as per Registration of Message sending entities enterprise on telecom operators DLT portal. If user has updated PE ID in his profile and this param is absent in http API, PE ID would be picked up from user's profile.

**TemplateID** SMS Template DLT ID as registered under registered header on telecom operator's DLT Platform.

**TM**  
(Optional) Telemarketer's ID. By default CISPL's TM ID would be added. It's recommended not to provide this parameter without consultation with BusinessSMS Team.

### Notes:

- Passing only 'ID' and 'Pwd' parameters will return your Ac Balance.
- Numbers would be paged if 'Text' parameter is absent or blank.
- SenderID or SenderNo would be taken from your account Details.



Works Wonder for your Business !!

## 2.2 HTTP Response

Contains String	Interpretation
'UserID, Password is required.'	'ID' and / or 'Pwd' parameters are blank.
'Authentication Failed.'	UserID or Password is incorrect.
'Your Account is not active'	Account is deactivated.
'Message Submitted'	Message to Phone number(s) submitted successfully.
'Insufficient Credit.'	Your account does not have sufficient balance to submit SMS batch.



Works Wonder for your Business !!

### 3. BusinessSMS WPF White Labeled .NET 4.5+ User Control.

- ☑ The modern WPF User Control may be used in WPF or Windows Forms application.
- ☑ Sample Visual Studio 2015 Windows Forms Integration project with source code available in Integration Kit.
- ☑ All settings and Templates saved in .json file and thus no database is required.
- ☑ The control is available in CISPLBulkSMS.dll. Add this dll as a reference in your project to use the user control.

The screenshot displays a Windows Forms application window titled "Form1". The interface is divided into two main sections: "SMS Login" and "Send SMS".

**SMS Login Section:**

- Host Name:** www.smsnmms.co.in
- User ID:** mybsuserid@myemail.com
- Password:** [Redacted]
- Buttons:** "Check Balance" and "Open SMS Portal"

**Send SMS Section:**

- Phone No:** [Empty text area]
- Sender ID:** BLKSMS
- Total Numbers:** 0
- SMS Text:** Last typed text in SMS Textbox
- Character Count:** 1 SMS (114 characters left) :: Total Characters: 46
- Append Text to SMS:** My SMS Signature
- Schedule Delivery:** 18/10/2019 12:34
- Buttons:** "Submit"

A vertical sidebar on the left side of the application is labeled "SMS Host and Login Settings".